

- c. Section: Asphalt shall be a minimum of two inches thick over four inches of crushed gravel, on a compacted subgrade. Concrete shall be four inches thick over two inches of crushed gravel, on a compacted subgrade.
- d. Shoulders: The pathway shall include a minimum of one-foot level shoulders on each side.
- e. Clearing: Trees and brush shall be cleared a minimum of fourteen feet (two feet each side of the pathway to a height of ten feet.
- f. Alignment: The pathway alignment shall follow the natural terrain of the land so as to minimize grading.
- g. Drainage: A discernable drainage ditch shall be constructed on the uphill side of a pathway. Culverts shall route stormwater runoff to the lower side of the trail to natural drainage ways.
- h. Grade: The maximum sustained grade shall be 12%. 15% grades may be allowed for short sections.
- i. Line of Sight: Minimum of 85 feet for grades less than 10% and 50 feet for grades greater than 10%
- j. Side Slopes: Pathways with downhill side slopes greater than 2:1 may, at the Director's discretion, require protective measures such as fencing.
- k. Pullouts Pullouts ten feet wide and 16 feet long should be constructed at significant lookout areas to allow for rest and aesthetic opportunities.

3.7 Pavement Cuts and Patches

The City of Cheney has adopted the Spokane County / City of Spokane Regional Pavement Cut Policy as its standard for the cutting and patching of existing roadways.